



CARPET SPECIFICATIONS

Technical:

| | |
|----------------------------|--|
| Product: | STITCH IN TIME |
| Construction: | 1/12 INFINITY |
| Gauge: | 12TH |
| Pile Height: | LOW: .156"/0.061 CM HIGH: .187" / .73 CM AVERAGE: .171" / .067 CM |
| Tufted Yarn Weight: | 32 OZ / 907 GM |
| Stitches Per Inch: | 12 |
| Fiber Content: | 100% - Solution Dyed Nylon |
| Density Factor: | 5737 LBS PER SYD / 4386 KG PER M ³ |
| Primary Backing: | Polypropylene |
| Secondary Backing: | Action Back |
| Width: | 12 ft. |
| Repeat: | 36" X 36" / 91 CM X 91CM |
| Colors: | BEDTIME BLUES, BLACK FRIDAY, GOLDEN AGES, MOMENT IN THYME, SCARLET O'ERA, & AFTERNOON COFFEE |

Testing Data:

| | |
|--|------------------|
| ASTM-E648 Flooring Radiant Panel | Class 1 |
| DOC-FF-1-70 Pill Test | Passes |
| AATC 134 Electrostatic Propensity | Less than 3.5 KV |
| E0622 Smoke Chamber | Less than 450 |

Disclaimer / Warranty:

CM Hospitality Carpets are manufactured and recommended for floor covering use only. With all quality carpet, colors may be subject to dye lot variations. If this product is not installed within our guidelines the product warranty may be voided. You can obtain our product installation guidelines on our company website (www.cmhospitality.com).

*Due to equipment limitations, patterned carpet may create visible lines in both the length and width of the carpet. It may not be detectible in a small sample and is not considered a manufacturing defect.

* With all patterned carpet, perfect pattern match may not be obtained at the seams. A reasonable pattern match may be obtained by using trained, experienced installers and by following the Manufacturer's installation procedures.

* For the warranties to apply, all Seam Sealers and Adhesives must be approved by CM Hospitality. We would recommend the use of CM300 Ultra Premium Adhesive and CM 1801 Seam Sealer.

* 10 Year Limited Wear Warranty - Please see complete warranty detail on our website.



2304 Dalton Industrial Court
Dalton, GA 30721

Tel: 877-261-6334
Fax: 877-261-6335