



## CM Hospitality CM 1801 Seaming Adhesive Specification Sheet

### I. Description:

CM Hospitality CM 1801 is a copolymer seam adhesive recommended for all types of carpet backings including vinyl (PVC). CM 1801 can be used in direct glue and double glue carpet applications. CM 1801 can be used to “butter” carpet edges in preparation for making seams for stretch-in carpet installations.

CM 1801 is solvent free and contains no hazardous or toxic chemicals. CM 1801 is 0 VOC as defined by the SCAQMD Proposition 65, Rule 1168. CM 1801 is solvent free, “Environmentally Safe” and “Installer Friendly”.

CM 1801 dries to an extremely strong bond, having tensile strength which exceeds traditional direct glue down, solvent based seam adhesives. CM 1801 can be applied to the edge using the same installation procedure and technique that is currently employed for all conventional seam adhesives. Place a 1/16" bead at the edge interface of first piece of material, while it lies in the spread floor covering adhesive, and then compress the second edge into the first. Apply the adhesive to only one side of the flooring.

Adhesive smears can be easily cleaned within 10-15 minutes by blotting with a clean cloth wet with soapy water. Dried adhesive can be removed with safety solvent. Do not soak the seam with either soapy water or solvent. Test all adhesive cleaners in an inconspicuous area to be sure the color/finish of the flooring will not be effected by the adhesive removers.

### II. Specific Technical Data:

- A. Latex Copolymer blend
- B. Color - white liquid, dries clear
- C. High strength, water resistant
- D. Solvent free, low odor (odorless when dry), Non-flammable liquid
- E. Shelf life: Up to one year in an unopened container. Keep from freezing

### III. Uses:

▪ Woven Polypropylene, unitaries, attached cushion and woven ▪ Polyurethanes including BioCell, Enhancers, Kangaback and Durafoam ▪ Vinyl's (Carpets and Resilient with cushion and hardbacks) ▪ Other Uses (Backing repairs, Binding tapes, Sample repairs, seam construction using “pin tape”, stretch-in or direct glue down installations)

- IV. Available in quarts.  
Clean-up: Wet - soapy water Dry – safety solvent

